

OPTIMA

Premium Soft Shackle

Optima 5 soft shackle made of premium Ultra-High Molecular Weight Polyethylene (UHMWPE). Its high visibility multi-color design and enhanced strength performance make it suitable for higher performance applications. This soft shackle is a lighter and smarter connection method, making it an excellent alternative to traditional cow hitches, steel shackles, or similar hardware. Whether onshore or offshore, Optima 5 soft shackle delivers outstanding performance.

The Optima 5 soft shackle also features a protective sheath with an attached coating. This function extends the lifespan of the soft shackle and provides additional protection for the connection.

Two types of protective sheaths are available: braided polyester sheath or webbing polyester sheath. The webbing sheath is lighter, allowing for quick and easy connections, making it a more economical choice. On the other hand, the braided sheath offers superior abrasion resistance and UV protection, making it suitable for harsh environments.















Technical Information

0.98 SPECIFIC GRAVITY

























	5.11	DOME:
Diameter	Opening Length	Minimun Breaking Strength
inch	inch	lbs
1/4	19	15,000
5/16	31	22,900
3/8	31	34,500
7/16	31	42,000
1/2	31	54,600
9/16	31	72,600
5/8	57	89,300
3/4	57	118,800
7/8	76	167,000
1	76	188,800
1 1/16	76	221,800
1 1/8	76	246,800
1 1/4	76	281,400
1 5/16	76	330,400
1 1/2	88	374,000
1 5/8	88	486,400
1 3/4	88	533,700
2	101	595,300
2 1/8	101	718,700

Diameter, weight and MBS are determined in accordance with CI1500-02. Custom size and length available by request.





















Durability Testing





