

# 3S PRO

## Rigging Rope

This 3-strand rigging rope not only resists the direct contact of rough tree barks, but also provides exceptional quality. It also has a long life span, making it a very cost-effective option. It also shares many benefits of our other popular ropes such as it's easy to splice and inspect.



Easy to use



Long lifespan



Cost-effective



Easy to splice



Easy to inspect



### Technical Information



**1.2**  
SPECIFIC GRAVITY



**1×3**  
CONSTRUCTION



**509°F (265°C)**  
MELTING POINT



**329°F (165°C)**  
CRITICAL TEMP



**10.17%**  
ELONGATION  
AT 30% BREAK



**0**  
WATER  
ABSORPTION

| Diameter | Material                 | Weight    | Breaking Strength | Minimum Strength<br>ISO Unspliced Rope |
|----------|--------------------------|-----------|-------------------|--|
| inch     |                          | lbs/100ft | lbs               | lbs                                    |
| 5/16     | Polyester/<br>Polyolefin | 2.5       | 2,900             | 3,200                                  |
| 3/8      | Polyester/<br>Polyolefin | 3.3       | 3,700             | 4,100                                  |
| 7/16     | Polyester/<br>Polyolefin | 4.4       | 4,800             | 5,300                                  |
| 9/16     | Polyester/<br>Polyolefin | 7.0       | 5,900             | 6,500                                  |
| 5/8      | Polyester/<br>Polyolefin | 10.0      | 8,100             | 9,000                                  |

Custom size and length available by request.



**ROPERS ROPE**



[sales@ropers.com.tw](mailto:sales@ropers.com.tw)



[www.ropersrope.com](http://www.ropersrope.com)