


X21E MAX

Kinetic Recovery Rope

X21E MAX with excellent matching of high-strength polyester and nylon is directly connected to the two vehicles to pull the trapped vehicles out through the movement of the vehicle itself.

Concurrently, X21E MAX is completely wrapped in the polyester sleeve, with a special coating at the eye spliced, which make it has excellent wear resistance.

- ▶ Soft eyelet is coated with polymer, giving you superior strength and wear resistance.
- ▶ High elongation, good energy absorption and effectively reduce vibration.
- ▶ Special coating, excellent wear resistance.



Abrasion
Resistance

Two
Recovery Points

High
Elongation

High
Efficiency



Specification

Diameter		Weight		Minimum Break Strength	
inch	mm	lbs/100ft	kg/100m	lbs	kg
9/16	14	10.8	16.0	14,600	6,600
5/8	16	13.2	19.6	17,600	8,000
3/4	18	18.4	27.4	21,600	9,800
7/8	22	22.2	33.1	29,000	13,200
1	24	25.5	38.0	33,500	15,200
1 1/4	30	36.9	54.9	48,400	22,000
1 3/8	34	47.4	70.5	62,000	28,200
1 9/16	38	59.1	88.0	77,500	35,200
1 11/16	42	72.2	107.5	94,600	43,000
1 7/8	46	86.7	129.0	113,300	51,500
2 1/16	50	102.4	152.4	124,700	56,700

▶ Specifications are for spliced strengths
Custom size and length available by request

ROPERS
RELIABLE TO THE CORE



ROPERS ROPE

✉ sales@ropers.com.tw

🌐 www.ropersrope.com