

OPTIMA 3

Hurricane/Cyclone Mooring Pendant

Optima3 Mooring Pendant is made of UHMWPE fiber, stands for lightweight, efficient and antifatigue. Optima3 has extremely low elongation and high breaking strength, which make better adapt to different marine environment. Provide bright and high visible styles; Matched with the movable prime wear-resistant sleeve to effectively reduce the contact friction with vessel, buoys and docks. Special abrasion resistant coating on the rope to prevent sand from being embedded.

- ▶ Ultra high strength with very low elongation
- ▶ Excellent strength-to-size ratio, efficient use
- ▶ Easy to splice
- ▶ Priming removable abrasion resistant sleeve
- ▶ Special abrasion resistant coating



Specification

Diameter		Soft Eye	Minimum Breaking Strength		Length
inch	mm	inch	lbs	kg	Feet
1/2	12	12.0	31,500	14,300	6
5/8	16	12.0	51,700	23,500	6
3/4	18	15.0	68,500	31,100	7
7/8	22	15.0	92,200	41,900	8
1	24	18.0	116,200	52,800	9

▶ Minimum Breaking Strength Are For ISO Unspliced Rope
Larger Available By Request



ROPERS
RELIABLE TO THE CORE



ROPERS ROPE
✉ sales@ropers.com.tw
🌐 www.ropersrope.com