

AURORA

General Purpose Semi-Static Rope

It is a semi-static rope certified to EN 1891A with perfect combination of high strength and low impact. It is flexible and lightweight. High tensile strength rope is suitable for technical working, safety work positioning or rescue environment. There is no any core/cover displacement so that during a rappelling procedure there will be practically no bunching up of the cover on the core. practically no bunching up of the cover on the core.

- ▶ Material: Core/Nylon, Cover/Nylon
- ▶ High strength
- ▶ Absorb the force generated during falling
- ▶ Easy to knot and use



High Quality



Low Elongation



Easy To Knot



Soft



▶ Can be customized

Specification

Diameter	Weight	Mass Of The Cover	Sheath Slippage	Minimum Breaking Strength	Elongation	Number Of Falls	Knotability	Impact Force	Standard
mm	g/m			kN				kN	
9	60	49%	0.00%	Free length: 23.0 Figure-eight knot: 15.5	2.9%	≥6	0.8	5.2	EN1891B
10.5	74	35%	0.00%	Free length: 33.0 Figure-eight knot: 21.0	3.0%	≥12	0.9	5.5	EN1891A
11	78	39%	0.00%	Free length: 33.3 Figure-eight knot: 21.1	2.8%	≥15	0.9	5.7	EN1891A

