

# T21

**PRO**

## Pulling / Stringing Line












This is a type of rope specifically engineered for rigging and tree work. It features a redesigned double-braid construction that significantly enhances overall strength. The rope combines a durable polyester cover with a polyester core, resulting in a high-strength, low-stretch, and torque-free rigging line, ideal for demanding applications in both tree care and rigging operations. No coating is softer and easier to handle.

 <b>Easy to handle</b>	 <b>Low elastic elongation</b>	 <b>Tightly woven polyester sheath</b>	 <b>UV resistance</b>
---	--	--	--



### Technical Information

 <b>Polyester CORE</b>	 <b>Polyester COVER</b>
 <b>1.38 SPECIFIC GRAVITY</b>	 <b>Double Braid STRUCTURE</b>
 <b>2.7% ELONGATION AT 30%</b>	 <b>0%-1% WATER ABSORPTION</b>
 <b>482°F (250°C) MELTING POINT</b>	 <b>350°F (177°C) CRITICAL TEMP</b>



 UV Resistance	★★★★★
 Wet Abrasion	★★★★★
 Dry Abrasion	★★★★★



Diameter	Weight	Minimum Strength Spliced Rope	Minimum Strength ISO Unspliced Rope
mm	lbs/100ft	lbs	lbs
1/4	2.1	2,000	2,200
5/16	3.2	3,100	3,400
3/8	4.5	4,800	5,300
7/16	6.1	6,500	7,200
1/2	8.2	8,800	9,700
9/16	11.0	11,300	12,400
5/8	14.0	13,900	15,300
3/4	18.0	17,300	19,000
7/8	27.1	25,400	27,900
1	34.0	33,300	36,600
1 1/8	45.3	41,000	45,100
1 1/4	53.9	48,700	53,600
1 5/16	60.8	55,000	60,500
1 1/2	73.3	63,800	70,200
1 5/8	85.9	74,100	81,500
1 3/4	104.0	88,400	97,200
2	124.0	105,000	115,500

Custom size and length available by request.

