

## TC-12 PRO

**Pulling Rope** 

TC-12 Pro is a 12-strand polyester braided rope that is highly renowned for its high strength and low elongation characteristics. Its length can be braided and extended infinitely to meet the specific needs of customers.

TC-12 Pro is not only easy to splice but also highly convenient to use. Furthermore, it features a wear-resistant polyurethane coating that provides exceptional abrasion resistance, making it a highly cost-effective option.





Available in long lengths



Special coating



Easy to splice



Easy to inspect



Soft



**Economical** 



to-weight ratio




## **Technical Information**




ELONGATION AT 30% BREAK

7.05%



1×12 CONSTRUCTION





Diameter	Weight	Strength Spliced Rope	Strength ISO Unspliced Rope
inch	lbs/100ft	lbs	lbs
5/16	3.3	4,600	5,100
3/8	3.9	6,400	7,100
7/16	6.3	8,400	9,300
1/2	8.0	11,200	12,400
9/16	9.9	13,000	14,400
5/8	12.2	16,700	18,600
3/4	17.4	22,000	24,400
7/8	25.9	32,600	36,200
1	38.6	46,900	52,100
1 1/16	44.0	56,300	62,600
1 1/8	52.3	64,500	71,700
1 1/4	59.8	74,800	83,100

Custom size and length available by request.