

# COBRA

## Abrasion Resistance Kinetic Recovery Rope

Thanks to the excellent extensibility of the Cobra, the huge energy generated by the towing vehicle. This energy is transferred to the trapped vehicle, so that can effectively rescue the vehicle in danger.

Cobra provides an excellent extension performance which also helps to reduce the shock during the towing. The rope can operate more stable and without damaging the vehicle accessories.

- ▶ Both side of eye splice has good wear resistance.
- ▶ Tensile performance up to 30% makes it more efficient and stable.
- ▶ Compared to static elongation, reduce the damage to the vehicle.



Abrasion  
Resistance



High  
Elongation



High  
Efficiency



Safe  
Durable



### Specification

| Diameter |    | Weight    |         | Minimum Break Strength |        |
|----------|----|-----------|---------|------------------------|--------|
| inch     | mm | lbs/100ft | kg/100m | lbs                    | kg     |
| 9/16     | 14 | 10.8      | 16.0    | 14,600                 | 6,600  |
| 5/8      | 16 | 13.2      | 19.6    | 17,600                 | 8,000  |
| 3/4      | 18 | 18.4      | 27.4    | 21,600                 | 9,800  |
| 7/8      | 22 | 22.2      | 33.1    | 29,000                 | 13,200 |
| 1        | 24 | 25.5      | 38.0    | 33,500                 | 15,200 |
| 1 1/4    | 30 | 36.9      | 54.9    | 48,400                 | 22,000 |
| 1 3/8    | 34 | 47.4      | 70.5    | 62,000                 | 28,200 |
| 1 9/16   | 38 | 59.1      | 88.0    | 77,500                 | 35,200 |
| 1 11/16  | 42 | 72.2      | 107.5   | 94,600                 | 43,000 |
| 1 7/8    | 46 | 86.7      | 129.0   | 113,300                | 51,500 |
| 2 1/16   | 50 | 102.4     | 152.4   | 124,700                | 56,700 |

- ▶ Specifications are for spliced strengths  
Custom size and length available by request

