

N08/N12

Nylon Mooring Line

A rope made of 100% high strength nylon fiber, which is widely used in ships. Due to the construction of the rope and the characteristics of the fiber itself, it has superior elongation, high strength and better impact resistance. The special 8-strand and 12-strand bonding method makes the rope have improved abrasion resistance. Its construction is round, soft and smooth, which is more convenient for manipulation and splicing.

- ▶ 100% Nylon, high strength
- ▶ Good elongation and impact resistance
- ▶ Firm, but also flexible
- ▶ Easy to splice and make loop



100%
Nylon



Good
Elongation



Impact
Resistance



Easy
To Splice



Specification

Diameter		Weight		Min. Breaking Strength	
inch	mm	lbs/100ft	kg/100m	lbs	kg
1 1/2	36	56	80	66,700	30,300
1 5/8	40	70	100	81,500	37,100
1 3/4	44	85	130	97,400	44,300
2	48	101	150	115,000	52,300
2 1/8	52	117	180	137,300	62,400
2 1/4	56	137	200	156,000	70,900
2 1/2	60	156	230	178,900	81,300
2 5/8	64	176	260	207,000	94,100
3	72	225	340	257,100	116,900
3 1/4	80	278	420	313,700	142,600
3 5/8	88	335	500	376,800	171,300
4	96	396	590	426,900	194,100
4 1/4	104	469	700	485,700	220,800

▶ Specifications are for unspliced strengths, strength will decrease by about 10% after splicing
Custom size and length available by request



ROPERS
RELIABLE TO THE CORE



ROPERS ROPE

✉ sales@ropers.com.tw

🌐 www.ropersrope.com